

P-5

Wash Light

Specifications		
Optics	Light source	44 x high-power 10W RGBW LEDs
	LEDs expected lifetime	50,000 hours*
Photometric	Interchangeable lens option	15°, 21° & 43°
	Light output	19,300 lm** (43° lens)
Features	Efficacy	46 lm/W
	Tilt	0 - 190°
Electrical	AC power	208 - 240V nominal 50/60Hz
	Maximum inrush current @ 240VAC	20A
	Maximum power consumption	450 W (all LEDs on)
	Typical power consumption	420 W (all LEDs on)
	Power factor	0.98 PF (230 V)
Programming and control	Protocol	USITT DMX512 A
	Setting and addressing	Wireless DMX (LumenRadio)
		RDM RFID
	Standalone mode	OLED graphical display / 4 buttons Software upgradable with SGM USB uploader cable (P/N:83062011) Quick color Up to 24 programmable scenes Standalone mode programmable by RFID
DMX channels	3, 4, 6, 8, 9 or 10	
Physical	Dimensions (L x H x W)	497 x 268 x 122 mm (19.6 x 10.6 x 4.8 in)
	Weight	8.9 kg (19.6 lbs.)
	Material	Aluminium
	Lens	PE and tempered glass front
	IP class	IP65
	Color options	White – RAL 9010 Black – RAL 9004 Custom color – any RAL
Installation	Mounting points	2 x two quarter-turn locking points for one or two Omega brackets
	Orientation	Any
	Rigging possibilities	Floor stand (included) or hanging (Omega clamps included)
	Safety features	Bottom mount for safety wire Minimum distance to combustible materials: 0.3 m (11 in.) Minimum distance to illuminated surfaces: 0.3 m (11 in.)
Thermal	Temperature range, Operating	-40° to +50°C (-40° to +122°F)
	Temperature range, Start-up	-20° to +50°C (-4° to +122°F)
	Temperature range, Storage	-40° to +80°C (-40° to +176°F)
	Humidity (max.)	98%
	Cooling	Active, forced air, temperature-regulated, low noise
Connections	DMX data in/out	IP65 Neutrik HD locking XLR 5-pin cable 0.5m, for DMX in and out
	Power	Power cable 1m with bare ends
Certified to Conforms to	CSA Std. C22.2 No. 166	
	UL Std. 1573	
	2014/35/EU: Low Voltage Directive	EN 60598-1, EN 60598-2-17, EN 62471, EN 60529
	2014/30/EU: EMC Directive	EN 55103-1, EN 55103-2, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3
RoHS2 Directive	2011/65/EU	
Included items	Included items	Floor stand (incl. screws) 2 pcs. Omega brackets Wireless DMX antenna User manual
	Fixtures	Order no: 80030517 - P-5 Wash, 43deg, Std, BL Order no: 80030537 - P-5 Wash, 43deg, Std, WH Order no: 80030540 - P-5 Wash, 43deg, Std, CU Order no: 80030515 - P-5 Wash, 21deg, Std, BL Order no: 80030538 - P-5 Wash, 21deg, Std, WH Order no: 80030541 - P-5 Wash, 21deg, Std, CU Order no: 80030518 - P-5 Wash, 15deg, Std, BL Order no: 80030539 - P-5 Wash, 15deg, Std, WH Order no: 80030542 - P-5 Wash, 15deg, Std, CU
	Lens/s	Order no: 83061118 - P-5, Lens kit (43°) Order no: 83061117 - P-5, Lens kit (21°) Order no: 83061116 - P-5, Lens kit (15°)
Fixtures and accessories	Cables	Order no: 83062011 - SGM USB uploader cable
	Brackets	Order no: 83060603 - BCC-2 Dual bracket
		Order no: 83060604 - BCC-4 Quad bracket
		Order no: 83060602 - Omega bracket
	Floorstand	Order no: 83060610 - Floorstand for i, P, Q and X series with 1/4-turn fasteners
	Barndoor	Order no: 83061119 - Accessory holder i-5 / P-5 Series
Order no: 83061120 - Barndoor 4-way, i-5/P-5/X-5/Q-7 series		
Order no: 83061121 - Barndoor 8-way, i-5/P-5/X-5/Q-7 series		
Flightcase	Order no: 83061122 - Color frame, i-5/P-5/X-5/Q-7 series	
	Order no: 82051501 - Flightcase for 4 pcs. of i-5/P-5/Q-7/X-5 Order no: 82051502 - Flightcase for 4 pcs. of i-5/P-5/Q-7/X-5 incl. barndoors	

*Figures provided by manufacturer and obtained under manufacturer's test conditions

**Goniometer Scan / SGM Illumination Lab 1.6.0.0

BL = Black (RAL 9004) / WH = White (RAL 9010) / CU = Custom Color (Any RAL color)